Wednesday, 12/7/2005 12:45:40 PM

User:

Kim Johnston

Process Sheet

Customer

: CU-DAR001 Dart Helicopters Services

Job Number **Estimate Number** : 25171

: 10298

P.O. Number This Issue

· N/A : 12/7/2005

: NC Prsht Rev.

First Issue

: N/A : 24372

: PURCHASED PARTS

Part Number **Drawing Number**

Drawing Name

: D25773 : D2577 REV E

Project Numbers **Drawing Revision**

: N/A

Material Due Date : NIK : 12/30/2005

: WEARPLATE

Qtv:

50 Um:

Each

Written By

Previous Run

Checked & Approved By Comment

Re-format; Incorporated D2577-101/-13 KJ/

COMMENT BRIOW

Additional Product

Job Number:



Seq. #:

Machine Or Operation:

Description:

1.0

PG



PURCHASING

slala



Comment: PURCHASING

Issue P/0: 0000267

Email or Ship DXF file to vendor

Laser Cut per Dwg D2577 flat pattern D2577-101

Material release note required

2.0

D25773F





1.0000 U(s)/Unit

50.0000 U(s) Total:

WEAR PLATE FWD

PACKAGING 1

PACKAGING RESOURCE #1-





Comment: PACKAGING RESOURCE #1 Receive & Inspect For Transit Damage

Ensure material release note is attached

4.0

3.0

QC6



DIMENSIONAL CHECK





Comment: DIMENSIONAL'CHECK

Inspect dimensions per template D2577-101T

SMALL & MEDIUM FAB RESOURCE 1 --



Deburr



Comment: SMALL & MEDIUM FAB RESOURCE 1

Dart Aerospace Ltd

W/O:		WORK ORDER CHANG	ES				
DATE	STEP	PROCEDURE CHANGE	Ву	Date	Qty	Approval Chief Eng / Prod-Mgr	Approval QC Inspector
16-01-11	4	Took I for temp inte. Identify AS D2577-101T (otiginal is missing)		Db - UI - ((/	More	06·01·11
			į.				

Part No:	PAR #:	Fault Category:	NCR: Yes No DQA:) Date: <u>%/03//</u>
<i>:</i>			QA: N/C Closed:	Date:

NCR:		W	ORK OR	DER NON-CONFORMANC	E (NCR)			·
		Description of NC		Corrective Action Section B		Verification	Ammrayal	Ammental
DATE	STEP	Section A	Initial Chief Eng	Action Description Chief Eng	Sign & Date	Section C	Approval Chief Eng	Approval QC Inspecto
							<u> </u>	
				,				
-								
		•						
			_					
								·

NOTE: Date & initial all entries

Wednesday, 12/7/2005 12:45:40 PM Date: Kim Johnston User: **Process Sheet** Drawing Name: WEARPLATE Customer: CU-DAR001 Dart Helicopters Services Part Number: D25773 Job Number: 25171 Job Number: Seq. #: Description: **Machine Or Operation:** NC BRAKE BRAKE NC 6.0 Comment: NC BRAKE 1-Form on brake as per Dwg D2577 using DT8155 and DT8179 2-Identify as D2577-3 INSPECT WORK TO CURRENT STEP QC5 7.0 Comment: INSPECT WORK TO CURRENT STEP LARGE FAB LARGE FABRICATION RESOURCE 1 8.0 Comment: LARGE FABRICATION RESOURCE 1 Weld hard surface using DT8308A & DT8308B as per Dwg D2577 · Qty Description Batch A/R 7560 Hardcoat Rod 9.0 QC9 **Comment: VISUAL WELDING INSPECTION** 10.0 POWDER COATING POWDER COATING Comment: POWDER COATING Powder Coat Grey Sandtex (Ref: 4.3.5.6) as per QSI 005 4.3 INSPECT POWDER COAT/CHEMICAL CONVERSION 11.0 QC3 Comment: INSPECT POWDER COAT/CHEMICAL CONVERSION 12.0 PACKAGING RESOURCE #1 Comment: PACKAGING RESOURCE #1 Identify and Stock Location: FV DOCUMENT CONTROL 13.0 Comment: DOCUMENT CONTROL 06/03/13 Inspection Level 21 0603 Page 2

Dart Aerospace Ltd

W /O:		WORK ORDER CH	ANGES	···		••	
DATE	STEP	PROCEDURE CHANGE	Ву	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector
						- - -	
Part No	:	PAR #: Fault Category:	NCR: Yes	No DQ	A:	Date: _	

NCR:			WORK ORDI	ER NON-CONFORMANC	E (NCR)		<u> </u>	
· // · · · · · · · · · · · · · · · · ·		Description of NC		Corrective Action Section B		Verification	A	A
DATE	STEP	Section A	Initial Chief Eng	Action Description Chief Eng	Sign & Date	Section C	Approval Chief Eng	Approval QC Inspector
						:		
						!		
						:		
		4						
				·				
								£

NOTE: Date & initial all entries

Dart Aerospace Ltd

W/O:		WORK	CORDER CHANGES					
DATE	STEP	PROCEDURE CHANGE		Ву	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector
ang i menganang ang ang								
Part No) :	PAR #: Fault Category	/: NCR:	Yes	No DQ	A :	Date:	


QA: N/C Closed: ____ Date: ___

NCR:			WORK ORDI	ER NON-CONFORMAN	CE (NCR)			
		Description of NC		Corrective Action Section B		Verification	A	A
DATE	STEP	Section A	Initial Chief Eng	Action Description Chief Eng	Sign & Date	Section C	Approval Chief Eng	Approval QC Inspector
					·			
							٠	
		٠.						
					*			
							•	
				,				

NOTE: Date & initial all entries

COPIED

7560 HARDCOAT WELD 4.0 LONG 0.063 TO 0.125 HIGH (TYP. 11 PLS.) WELD AFTER BENDING AS ILLUSTRATED PER DT8308



04 TT






D2577-1 & D2577-3 WEARSHOE MAKE FROM D2577-11 AND D2577-13 RESPECTIVELY FINISH: POWDER COAT GREY (4.3.5.6) PER DART QSI 005 4.3 TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED

	THE PARTY OF THE P	
D2941-300 SHWAYDER WEAPADS (8 PLACES) A 1.50 (TYP)	0.12 (TYP)	SECTION A-A SCALE 1:5 R2.00 D2941-300 (REF) REMOVE POWDER COAT FROM THESE SURFACES

D2577-21 & D2577-23 WEARSHOE
MAKE FROM D2577-11 AND D2577-13 RESPECTIVELY
FINISH: POWDER COAT GREY (4.3.5.6) PER DART QSI 005 4.3
TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED

) VOIS30	DRAWN BY	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA
 CHECKE	ED APPROVED	DRAWING NO. REV. E
 ^	4	D2577 SHEET 1 OF 5
 DATE		TITLE SCALE
00.0	00.09.22	WEARSHOE 1:10
 Α	96.09.16	NEW ISSUE
 В	96.12.04	ADD HARDCOAT WELDS
 С	97.05.30	CHANGE HOLES TO OBROUNDS
 D	98.08.17	CORRECTED DIMENSIONS ON -1 & -3
 m	00.09.22	ADD D2577-101/-11/-13 INCORPORATE DE09176




D2577-101 FLAT PATTERN

BREAK ALL SHARP CORNERS 0.010 TO 0.020

MATERIAL: AISI 1010-1025 OR ASTM A36/A366/A569/A570

SERIES STEEL 0.063 THICK

TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED




D2577-11 & D2577-13 LONGITUDINAL BEND MAKE FROM D2577-101 TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED






00.09.22	DATE	+	СНЕСКЕЙ	9	() () () () () () () () () ()
		#	APPROVED	S	
WEARSH	חתה	D2577	DRAWING NO		



SCALE S

1:10



D2577-5 WEARSHOE

BREAK ALL SHARP CORNERS 0.010 TO 0.020

MATERIAL: AISI 1010-1025 OR ASTM A36/A366/A569/A570

SERIES STEEL 0.063 THICK

FINISH: POWDER COAT GREY (4.3.5.6) PER DART QSI 005 4.3 TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED






f	S	HAWKESBURY, ONTARIO, CANADA
снескер	APPROVED.	DRAWING NO.
¥		D2577 SHEET
DATE		TITLE
00.09.22		WEARSHOE

OF: S

D2577-7 FLAT PATTERN



D2577-7 LONGITUDINAL BEND

SEE DETAIL C ON PAGE 5

D2577-7 WEARSHOE

BREAK ALL SHARP CORNERS 0.010 TO 0.020

MATERIAL: AISI 1010-1025 OR ASTM A36/A366/A569/A570

SERIES STEEL 0.063 THICK

POWDER COAT GREY (4.3.5.6) PER DART QSI 005 4.3 FINISH: TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED







WEARSHOE 1:10		0.09.22
TITLE	-	ATE
D2577 SHEET 4 OF 5	4	耳
DRAWING NO. REV. E	APPROVED	HECKED
HAWKESBURY, ONTARIO, CANADA		 `
DADT ADDONDACE ITD	UKAWN BY	COICN A







DESIGN	DRAWN BY	DART AEROSP HAWKESBURY, ONTAR	
CHECKED	APPROVED	DRAWING NO.	REV. E
GH .	1 #	D2577	SHEET 5 OF 5
DATE		TITLE	SCALE
00.09.22		WEARSHOE	1:10

DETAIL B (SCALE 1:1)






DETAIL C (SCALE 1:1)



SECTION D-D (SCALE 1:1)



SO WE FRIN iper . J. I WITH

25171

Copyright @ 1996 by DART AEROSPACE LTD

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.





New Zestand Steel Limited Glenbrook, South Aucktand Poetal: Private Bay 92121, Aucktand, New Zestand Telephones: (09) 375 8996 / 375 8111 Aucktand (08) 235 8089 / 236.3535 Wandru Fax; (09) 375 8859



CUSTOMER	Wilkinson				' 50) 3.	23	a.	IO	16	S	PEE	FICAT	ION	ASTM	A1608 (S Type A	_	_			c	ERTIF:	CATE No TC112397		
CUSTOMER OWN	90-21N-68	6	• 1								P	ROD	DOT-		CRA W								PAGE 1 of 1			
MILL OIN	480737										D	MEI	NSION	8	0.055"	× 48" ×	Cell					 	ATE	89 June 2005		
						CHEM	IÇAL (COMP	OSITIC	N PERC	ENT		ČA Sp. (m) z 10		· · · · · · · · · · · · · · · · · · ·	****	ME	CHANICAL	TESTS (T	EST SPECIFI	CATION -	Ц.	STMA			
PACK NUMBER	HEAT No	C	Si	Mn	P	s	Cu	Ni	Cr	Мо	V .	W	Ti	Al	B , N2	CE(BEND	YELD	T.S.	T	HARDNESS					
	1.51110	_	x100)					x1	000		•			×10000	x100	180°		1.0.	G.L.=	HRB		()	LENGTH (feet)	•	
R9-459713-00	641758	4	TR	1	4	16	13	19	10	5	3	1	1		i		Good			 	54	+		1585		
R9-459714-00	641758	4	TR	1	4	16	13	19	10	5	3	1	1		1 :		Good			Ĭ	54	1		1457		
R9-459715-00	641513	5			9	18	12	17	15	1	6	1	1				Good			Į.	48			1375		
R9-459716-00	641513	5			9	18	12	17	15	1	6	ı	- 1				Good				48			1473		
R9-459717-00	641756	5	TR	Z 0	12	19	12	18	19	1	7 !	1	1			'	Good	į			48	1		1631		
R9-459718-00	641756	5		20	12	19	12	18	19	1	7 ;	ı į					Good				48	İ		1093		
R9-459719-00	641756	ŀ	TR	1	12	19	12	18	19	1	7	1	1		1 :	1	Good				50	ł		1562		
R9-459720-66	641756	1	; TR	1		19	12	18	19	1	7	1	1			1	Good				50	1		1535		
R9-460380-00	641761	ł	TR	1	13	17	12	18	25	5	8	1	1				Good				50			1581		
R9-466381-60	641758	1	TR	1	4	16	13	. 19	10	5	3	1	1			1	Good				49			1562		
R9-460382-00	641758	4	TR	18	4	16	13	19	16	5	3	1	1				Good	!			49			1503		
R9-461458-00	642309		TR	18	10	20	- 11	17	19	1	6	1	1				Good	;		1						
J. KV-961458-00	642309		TR	18	10	20	- 11	17	19	1	6	1	1		<u> </u>	<u></u> .	Good				48	1.		1785		

YIELD : GAUGE LENGTH (G.L.) PLASTIC STRAIN RATIO (r) (A)=0.2% PROOF STRESS (A)=0.2% PROOF STRESS ; (A)=200mm (B)=LOWER YIELD STRESS ; (B)=50mm (C)=80mm (A)=r0 (B)=r90 (E)=2" (C)=r45 (D)=(r0+r90+2r45) / 4

(D)=5.65 ? So

IMPACT TEST (A)=10mm x 10mm (B)=7.5mm x 10mm

(C)=5mm x 5mm (D)=2.5mm x 10mm (E)=5mm x 10mm CARBON EQUIVALENT VALUE (CE)

(A)=C+Mn/6 (B)=C+Mn/6+(Cr+V+Ma)/5+(Cu+Ni)/15

(C)=C+Mn/6+Si/24 (D)=

WE HEREBY CERTIFY THAT THE MATERIAL DESCRIBED HEREIN HAS BEEN TESTED AND INSPECTED WITH SATISFACTORY RESULTS IN ACCORDANCE WITH THE REQUIREMENTS OF THE ABOVE-SPECIFICATION

(F)≃8°

OC METALLURGIST

APPROVED Satish Misra

INDUSTRIAL (PS0323DI001: 641756

